

SlimLite Elegant LED Design Solution

- Elegant and compact design
- Different colour models
- Stainless steel housing
- Minimal heat emission
- Lifetime of 50.000 hours








The light runs through a programme of single and mixed colours (green, red, and blue) in a therapeutically relaxing pattern.

	T	T
DESCRIPTION	SLIMLITE Ø52 MM ARTICLE NO.	SLIMLITE Ø83 MM ARTICLE NO.
Cool white LED light	21-1950-5	21-1970-5
Warm white LED light	21-1952-5	21-1972-5
Blue LED light	21-1953-5	21-1973-5
Colour changing LED light	21-1951-5	21-1971-5
5Colour changing / stop LED light	21-1955-5*	21-1975-5*
Colour changing / stop LED light incl. connector and touch	21-1954-5*	21-1974-5*
Colour changing / stop LED light incl. connector and LED button	21-1956-5*	21-1976-5*

^{*} Stand alone system with built in electronics, not to be connected to control box.

All models include: Transformer for 230V AC, 50HzFront and rear sealsStainless steel housing and front.


Energy



Peace



Comfort



Dimensions in mm.



This touch is included in article no. 21-19x4-5



This LED button is included in article no. 21-19x6-5

FEATURES & BENEFITS

- All LED lights are equipped with a premounted transformer (230V AC / 12V AC). The transformer is extremely compact (H=29 mm L=32.5 mm W=27.3 mm) and can be easily inserted through the drilled hole, from the front of the tub. This will save time in your production
- All LED lights can be equipped on most existing control panels via a 230V light outlet
- All Slimlite Ø52 mm LED lights have 18 diodes and a front diameter of 52 mm
- All Slimlite Ø83 mm LED lights have 51 diodes and a front diameter of 83 mm
- All LED lights have an expected life time of 50.000 hours
- All LED lights are manufactured to have min. protection class IPX5 from the back and IPX8 from the front
- All LED lights are supplied with front and rear seals
- All LED lights have almost no heat emission and require no water cooling





